




GEOHERMAL INSULATED TEGA PIPING SYSTEM EF COUPLERS, IPS

30 PSI @ 73 Degrees Maximum Sustainable Working Pressure

Available in PE & PP



Nominal Pipe Size	d/2	"D"	"L"	Unit Weight	Item Code
3"	3.500"	4.000"	22.000"	2.300"	30.JM1.11.27.0088
4"	4.500"	4.900"	22.000"	2.450"	30.JM1.11.27.0114
6"	6.630"	7.500"	22.000"	7.000"	30.JM1.11.27.0168
8"	8.630"	9.650"	22.000"	6.600"	30.JM1.11.27.0219
10"	10.750"	12.000"	22.000"	16.100"	30.JM1.11.27.0273
12"	12.750"	13.700"	22.000"	15.000"	30.JM1.11.27.0323
14"	14.000"	15.350"	22.000"	24.200"	30.JM1.11.27.0355
16"	16.000"	17.500"	22.000"	30.860"	30.JM1.11.27.0406
18"	18.000"	19.500"	22.000"	32.800"	30.JM1.11.27.0457
20"	20.000"	21.600"	22.000"	39.500"	30.JM1.11.27.0508
22"	22.000"	24.000"	22.000"	54.000"	30.JM1.11.27.0558
24"	24.000"	26.700"	22.000"	84.000"	30.JM1.11.27.0609
28"	28.000"	30.700"	22.000"	91.700"	30.JM1.11.27.0711
30"	30.000"	33.000"	22.000"	113.300"	30.JM1.11.27.0762
32"	32.000"	35.400"	22.000"	137.000"	30.JM1.11.27.0812

(*) Special Diameters Available Upon Request

() Special Lengths Available Upon Request**

STRONGBRIDGE INTERNATIONAL INC.

PO Box 58177, Jacksonville FL 32241
 Phone: (904) 607-6384 Fax:(904) 565-2776
www.strongbridge.us

STRONGBRIDGE INTERNATIONAL (CANADA) INC.

200 North Service Road West, Unit 1 Suite 381
 Oakville, Ontario L6M 2Y1
 Phone (416) 795-8962
www.strongbridgecanada.com

ELECTROFUSION FITTINGS MUST BE INSTALLED BY QUALIFIED INDIVIDUALS TRAINED AND CERTIFIED IN
 ELECTROFUSION INSTALLATION PROCEDURES.