




# GEOHERMAL INSULATED TEGA PIPING SYSTEM EF COUPLERS, IPS

30 PSI @ 73 Degrees Maximum Sustainable Working Pressure

Available in PE & PP



Nominal Pipe Size	d/2	"D"	"L"	Unit Weight	Item Code
3"	3.500"	4.000"	22.000"	2.300"	30.JM1.11.27.0088
4"	4.500"	4.900"	22.000"	2.450"	30.JM1.11.27.0114
6"	6.630"	7.500"	22.000"	7.000"	30.JM1.11.27.0168
8"	8.630"	9.650"	22.000"	6.600"	30.JM1.11.27.0219
10"	10.750"	12.000"	22.000"	16.100"	30.JM1.11.27.0273
12"	12.750"	13.700"	22.000"	15.000"	30.JM1.11.27.0323
14"	14.000"	15.350"	22.000"	24.200"	30.JM1.11.27.0355
16"	16.000"	17.500"	22.000"	30.860"	30.JM1.11.27.0406
18"	18.000"	19.500"	22.000"	32.800"	30.JM1.11.27.0457
20"	20.000"	21.600"	22.000"	39.500"	30.JM1.11.27.0508
22"	22.000"	24.000"	22.000"	54.000"	30.JM1.11.27.0558
24"	24.000"	26.700"	22.000"	84.000"	30.JM1.11.27.0609
28"	28.000"	30.700"	22.000"	91.700"	30.JM1.11.27.0711
30"	30.000"	33.000"	22.000"	113.300"	30.JM1.11.27.0762
32"	32.000"	35.400"	22.000"	137.000"	30.JM1.11.27.0812

**(\*) Special Diameters Available Upon Request**

**(\*\*) Special Lengths Available Upon Request**

**STRONGBRIDGE INTERNATIONAL INC.**

10920 Baymeadows Road, Unit 27-302

Jacksonville, FL 32256

Phone: (904) 607-6384 Fax:(904) 565-2776

[www.strongbridge.us](http://www.strongbridge.us)

**STRONGBRIDGE INTERNATIONAL (CANADA) INC.**

200 North Service Road West, Unit 1 Suite 381

Oakville, Ontario L6M 2Y1

Phone (416) 795-8962

[www.strongbridgecanada.com](http://www.strongbridgecanada.com)

TEGA ELECTROFUSION FITTINGS MAY ONLY BE INSTALLED BY TECHICIANS CERTIFIED BY STRONGBRIDGE INTERNATIONAL INC. OR ITS DESIGNATED AND APPROVED AGENTS. CONTACT STRONGBRIDGE INTERNATIONAL FOR CURRENT CERTIFICATION DETAILS AND REQUIREMENTS.

Copyright 2009 Strongbridge International Inc. All rights reserved. Information subject to change without notice. E. & O.E.

Subject to Strongbridge International Inc. Limited Warranty, available at [www.strongbridge.us](http://www.strongbridge.us)



